

SPECIFICATIONS

| | |
|------------------------|-------------------------------------|
| Image Sensor | 1/4" CCD |
| PICTURE ELEMENTS | EIA: 512H x 492V, CCIR: 512H x 582V |
| HORIZONTAL RESOLUTION | 380 Lines |
| Min Illumination | 2 Lux |
| HORIZ. SYNC.FREQUENCY | EIA: 15.734KHz - CCIR: 15.625KHz |
| VERTICAL FREQUENCY | EIA: 60Hz - CCIR: 50Hz |
| CLOCK FREQUENCY | EIA: 19.0699MHz - CCIR: 18.9375MHz |
| SCANNING SYSTEM | 2:1 INTERLACE |
| S/N RATIO | 46dB |
| ELECTRONIC SHUTTER | 1/100,000 sec. (Linear) |
| LENS | 5.5mm f3.5 |
| White Balance | Auto tracing |
| Backlight Compensation | ? |
| Gain control | Auto |
| VIDEO OUTPUT | 1Vp-p, 75 Ohms |
| GAMMA. | 0.45 |
| MIRROR REVERSE PICTURE | NO |
| DIGITAL ZOOM | NO |
| Dimensions | 22 x 26mm |
| POWER SUPPLY | 12VDC (+/- 0.5V) @ 85ma |
| STORAGE TEMPERATURE | -30 to +60°C |
| OPERATING TEMPERATURE | -10 to +45°C |